

Weather Transmitter		WXT520									0											
Measurement parameters	Wsd+RH+T+P+R	A																				
Communication interface	SDI-12 v 1.3, 1200 baud, 7,E,1	A	A	A																		
	RS-232, Standard ASCII auto, 19200 baud,8,N,1	A	A	B																		
	RS-485, Standard ASCII polled, 19200 baud, 8,N,1	A	A	C																		
	RS-422, Standard ASCII auto, 19200 baud, 8,N,1	A	A	D																		
	RS-422 NMEA 0183 v3.0, 4800 baud, 8,N,1	A	A	E																		
	<i>USB/RS-232, 1.4 m USB / M12 cable, ASCII auto, 19200,8,N,1</i>	<i>A</i>	<i>A</i>	<i>F</i>																		
	<i>USB/RS-485, 1.4 m USB / M12 cable, ASCII polled, 19200,8,N,1</i>	<i>A</i>	<i>A</i>	<i>G</i>																		
Enhancements	None									0												
	<i>Heating for wind and rain measurements</i>									<i>1</i>												
Connector	No connector, bushing & grounding accessories									A												
	<i>8-pin M12 male connector and bushing & grounding accessories</i>									<i>B</i>												
Cable	No Cable									A												
	<i>Shielded 2 meters long 8-pin M12 cable</i>									<i>B</i>												
	<i>Shielded 10 meters long 8-pin M12 cable</i>									<i>C</i>												
	<i>Shielded 40 meters long 14-pin cable, open end wires</i>									<i>D</i>												
	<i>Shielded 10 meters long 8-pin M12 cable, connectors on both ends</i>									<i>E</i>												
Installation accessories	None									0												
	<i>Mounting kit</i>									<i>1</i>												
	<i>Bird spike</i>									<i>2</i>												
	<i>Mounting kit and Bird spike</i>									<i>3</i>												
Supporting software	None									0												
	<i>Service Pack 2: Vaisala Configuration Tool for Windows, USB Service cable</i>									<i>1</i>												
Manual language	No manual									A												
	English									B												
Packing	Standard										0											
Selections in bold are included in the prices of the basic versions.										TOTAL	0											
<i>Selections in italic are available at an extra price.</i>										QTY												
										TOTAL VALUE												
Example of order code with typical settings:																						
<table border="1"> <tr> <td>WXT520</td> <td>A</td> <td>A</td> <td>A</td> <td>0</td> <td>A</td> <td>A</td> <td>0</td> <td>0</td> <td>A</td> <td>0</td> </tr> </table>												WXT520	A	A	A	0	A	A	0	0	A	0
WXT520	A	A	A	0	A	A	0	0	A	0												
End customer:	_____																					

WXT520 Spare parts & Accessories

220614	Service Pack 2: Vaisala Configuration Tool for Windows, USB Service cable
218817SP	WXT520 Radiation shield set
WXTBOTTOMSP	WXT520 Bottom assembly (with BIF card, M12 connector, screws w. O-rings)

WXT510/520 Spare parts & Accessories

220782	USB RS-232/485, 1.4 meters USB / M12 cable
222287	Shielded 2 meters long 8-pin M12 cable
222288	Shielded 10meters long 8-pin M12 cable
217020	Shielded 40 meters long 14-pin cable, open end wires
215952	10 meters long 8-pin M12 cable, connectors on both ends
WXTPTUSP	WXT PTU module
222109	Bushing & grounding accessory kit
212792	Mounting kit (improves classification from IP65 to IP66)
WSP150	Surge protector, no connectors
WSP152	Surge protector for host PC (e.g. USB connection) inc. M12 connectors. Suitable with 220782 and 215952.
212793	Bird kit

WXT510 Spare parts & Accessories

215194	Service Pack 1: Vaisala Configuration Tool, Weather Measurements (software and RS-232 WXT510 service cable)
221523	M8 adapter to WXT510 Service connector (use with Service pack 2)